



DP-5000

PC Based Compact Printer

Versatile printer for small work space

Large label roll for more efficient pre-packing

Adjustable operator display

High speed printing



DP-5000

DIGI Retail Scale and Labeling Systems
NEW BRUNSWICK INTERNATIONAL, INC.

Features


- Front label loading mechanism makes label changing easy
- Large label roll for more efficient pre-packing



- Operator display with touch screen panel can be adjusted to fit operator's viewing preference
- Colourful 8.4" TFT touch screen display is eye-catching and easy to use



- High printing resolution at 300dpi on 80mm label




More features...

Remote diagnostics, email alert, printing graphics on label and receipt, Open Database Connectivity (CDBC) and help mode for operators

Options

- Attractive and informative electronics display provides seamless updating of product information with every printer database change



- Linerless labels reduces paper waste and is environment friendly



Specifications

Items Printed on Label

- Price
- Content
- Multi-Barcode
- Discount Price
- Commodity Name
- Ingredients
- Special Message
- Shop Name
- Dates : Packed on Date, Consume by Date
- Times : Packed on Time, Consume by Time
- Image
- Frames
- Nutrifacts
- Country of Origin
- Others

Items Printed on Receipt (Report)

- Shop Name
- Commodity Name
- Price
- Total Price
- Discount Price
- Sub Total
- Tax
- Grand Total
- Total Item Quantity
- Barcode
- Date
- Time
- Clerk Number
- Receipt Number
- Machine Number



Dimension	422.6 mm x 220 mm x 407.5 mm	
CPU	iMX31 533MHz	
Memory	Factory default 256MB / 512 MB DDRAM 133MHz SD Card 8GB	
Display	8.4" TFT SVGA with Touch Panel	
Operator Display	+/- 30 degree left and right; 90 degree up and down	
Weigh	10.8kg	
Printing Mechanism	Print Method	Thermal Printing
	Paper Width	Maximum 80mm
	Print Resolution	300dpi
	Print Speed	150mm/s
Media (Label)	Max Roll Diameter (Outer)	125mm
	Inner Roll Diameter	40mm
Barcode Type	Interleave 2 of 5, EAN-8, EAN-13, EAN-128, RSS, PDF417 (for receipt only)	
Power Source	AC 100V / 220V	
Power Consumption	80W	
Operating Humidity	15% ~ 85% RH Non-Condensation	
Operating Temperature	-10°C to +40°C	
I/O Interface	IUSB, Ethernet 10/100 Base-T, RS-232 (Mini DIN), SD pocket	
Optional Interface	Wireless LAN (IEEE 802.11b/g)	

CE • Specifications are subject to change without prior notice



DIGI Retail Scale and Labeling Systems NEW BRUNSWICK INTERNATIONAL, INC.

76 Veronica Avenue
Somerset, NJ 08873
TEL: (732)-828-3633
FAX: (732)-828-4884

530 West Central Avenue, Suite C
Brea, California 92821
TEL: (714)-671-7911
FAX: (714)-671-0798

website: www.nbidigi.com